

# MINIFIBERS, INC.

## ELASTOMERIC ROOF MASTIC CONTAINING SHORT STUFF® POLYETHYLENE E380F

### MATERIALS:

	<u>% by weight</u>
Natrosol - 250MR - 3%.....	12.00
Water.....	1.00
Tamol 850.....	0.40
KTPP.....	0.10
Ethylene Glycol.....	2.00
Nopco NXZ.....	0.15
T <sub>1</sub> O <sub>2</sub> - R-960.....	6.00
MiniFIBERS' SHORT STUFF® Polyethylene E380F.....	2.00
Duramite®.....	34.50
Kadox 515.....	4.00

Grind and mix for 15 minutes, then let down with the following:

Emulsion E-1685.....	35.50
Texanol.....	1.00
Skane M8.....	0.16
Nopco NXZ.....	0.15
NH <sub>4</sub> OH.....	0.07
Water.....	<u>1.00</u>
	100.03

Mix for 15 minutes to a smooth consistency.

### PHYSICAL PROPERTIES:

Weight per Gallon..... 12.28 lbs.

Viscosity..... 30,000 cps

Application.....Squeegee, trowel, brush, and airless spray.

- 1) Excellent resistance to dirt pickup.
- 2) Excellent adhesion to a variety of substrates (wood, urethane foam, galvanized steel, asphalt, roof shingles, etc.)
- 3) Good resistance to ponded water.
- 4) Superior ultraviolet resistance properties.

Information in this bulletin is the best available to us and is believed to be correct.  
No warranty is expressed or implied regarding its accuracy on the use of the product.  
Nothing herein constitutes permission or recommendation to practice any invention  
covered by any patent without a license from the owner of the patent.

SS-09

TELEPHONE 423/282-4242  
2923 BOONES CREEK ROAD  
JOHNSON CITY, TENNESSEE 37615-4662