

MiniFIBERS, INC.

**FIBERED MASONRY BLOCK FILLER
BASED ON AMSCO RES 3011 AND/OR RES 3077
CONTAINING SHORT STUFF® POLYETHYLENE E400M**

<u>MATERIALS:</u>	<u>Pounds</u>	<u>Gallons</u>
Water.....	275.0	33.00
Colloid® 681F.....	3.0	.40
Natrosol 250MR.....	5.0	.46
Polywet ND-2.....	4.7	.50
AMP-95.....	1.0	.15
Igepal CO-610.....	2.0	.25
Super Ad-It.....	1.0	.12
Ethylene Glycol.....	27.9	3.00
MiniFIBERS' SHORT STUFF® Polyethylene E400M.....	7.0	.93
Tronox CR-800.....	25.0	.73
325 Mesh Waterground Mica.....	25.0	1.06
Duramite®.....	300.0	13.29
Imsil® A-15.....	300.0	13.59
Disperse for 20 to 30 minutes slow mill, then add:		
Texanol.....	9.9	1.25
AMSCO RES 3011 and/or RES 3077.....	<u>324.0</u>	<u>36.00</u>
TOTAL.....	1310.5	104.73

PHYSICAL PROPERTIES:

Viscosity.....	110-115 KU
Weight per Gallon.....	12.5 lbs.
% Solids - By Weight.....	64.1%
By Volume.....	46.0%
PVC.....	61.3%

Information in this bulletin is the best available to us and is believed to be correct.
No warranty is expressed or implied regarding its accuracy on the use of the product.
Nothing herein constitutes permission or recommendation to practice any invention
covered by any patent without a license from the owner of the patent.

MiniFIBERS, INC.