

MINIFIBERS, INC.

ELASTOMERIC ROOF COATING WHITE CONTAINING SHORT STUFF® POLYETHYLENE E505F & ESS50F

<u>Raw Material</u>	<u>Pounds</u>	<u>Gallons</u>
Water.....	151.4	18.14
Jaguar HP 96.....	6.0	0.40
Mix for 5 minutes, then add:		
Ammonia 19%.....	2.0	0.50
Propylene Glycol.....	15.0	1.75
Surfynol 104E.....	2.0	0.25
Dehydran 1620.....	5.0	0.50
Byk 1610.....	2.0	0.25
Mix for 5 minutes, then add:		
Titanium Dioxide Rutile Grade.....	65.0	2.00
Grind to 7H.		
Attagel 50.....	3.0	0.15
Kadox 915.....	25.0	0.70
Marble White.....	400.0	17.77
Grind to 6H.		
MiniFibers SHORT STUFF® E505F.....	7.5	
MiniFibers SHORT STUFF® ESS50F.....	2.5	
Mix for 5 minutes, then add:		
Rhoplex EC-1791.....	490.0	57.00
Texanol.....	6.5	0.82
Mergal k10N.....	2.0	0.25
Byk 1610.....	<u>2.0</u>	<u>0.25</u>
TOTAL.....	1186.9	100.73

PROPERTIES:

pH.....	9.0 to 9.5
Viscosity.....	100 to 110 KU @ 77°F
Grind.....	6H
Weight per Gallon.....	11.75 lbs
Pigment Volume Concentration (PVC).....	40%
Solids by Volume.....	51.2%
Solids by Weight.....	65%

Information in this bulletin is the best available to us and is believed to be correct.
No warranty is expressed or implied regarding its accuracy on the use of the product.
Nothing herein constitutes permission or recommendation to practice any invention
covered by any patent without a license from the owner of the patent.

MINIFIBERS, INC.

TELEPHONE 423/282-4242
2923 BOONES CREEK ROAD
JOHNSON CITY, TENNESSEE 37615-4662