

# MINIFIBERS, INC.

## ELASTOMERIC FIBERED ROOF COATING, WHITE CONTAINING SHORT STUFF® POLYETHYLENE E505F & ESS50F

<b><u>MATERIALS:</u></b>	Pounds	Gallons
Water.....	151.40	18.140
Natrasol 250 HBR.....	6.00	0.400
Mix 10 minutes, then add:		
Ammonia 19%.....	2.00	0.375
Mix 5 minutes, then add:		
Polypropylene Glycol.....	7.50	0.880
Surfynol 104E.....	2.00	0.250
Dehydran 1620.....	5.00	0.500
Drew L-475.....	2.00	0.250
Mix 5 minutes, then add:		
Tiona 464 Titanium Dioxide.....	65.00	2.000
Attagel 40.....	3.00	0.150
Grind to 7 Hegman, then add:		
Kadox 915.....	25.00	0.700
Wollastinite.....	25.00	0.700
Grind to 5+ Hegman, then add:		
Water.....	41.65	5.000
Calcium Carbonate.....	400.00	17.770
Grind to 4+ Hegman. Stir in the following fibers:		
MiniFIBERS' SHORT STUFF® Polyethylene E505F.....	5.00	
MiniFIBERS' SHORT STUFF® Polyethylene ESS50F.....	2.50	
Mix 5 minutes, then add:		
Rohm Haas 1791 Polymer.....	500.00	58.000
Texanol.....	7.90	1.000
Mergal K10N.....	2.00	0.250
Noucide 404D.....	2.00	0.160
Drew L-475.....	2.00	0.250
TOTALS.....	1256.95	106.775

**PHYSICAL PROPERTIES:**

Viscosity, KU.....	120 ±5
Weight per Gallon, lbs.....	11.77
pH.....	9.0-9.5
PVC.....	41.5%

Information in this bulletin is the best available to us and is believed to be correct.  
No warranty is expressed or implied regarding its accuracy on the use of the product.  
Nothing herein constitutes permission or recommendation to practice any invention  
covered by any patent without a license from the owner of the patent.

TELEPHONE 423/282-4242  
2923 BOONES CREEK ROAD  
JOHNSON CITY, TENNESSEE 37615-4662