

ADMIXUS®

Technical Data Sheet

ADMIXUS® HPC

General Description: A high strength, lightweight polyethylene filament with one of the highest strength-to-weight ratios of any man-made fiber.

Standard Filament Sizes: 2.2 denier per filament (dpf)

Standard Cut Lengths: 1/4" and 1/2"
(6mm and 13mm)
Other lengths may be available upon request.

Shrinkage, Boiling Water: <1.0%

Tenacity: 3 GPa

Elongation: <4.0%

Modulus: 114 GPa

Initial Moisture Content: <3.0%

Average Moisture Regain of Polyethylene: <1.0%

Specific Gravity: 0.97 g/cm³

Effect of Heat: Melts at 144-152°C / 290-306°F.
Decomposes at >300°C / 572°F.

Other Characteristics: High resistance to chemicals. Low moisture absorption. High resistance to ultraviolet light. Excellent vibration dampening. Highly resistant to flex fatigue. Low coefficient of friction. Good resistance to abrasion. Low dielectric constant.

Packaging: Fiber is packaged in corrugated boxes with polyethylene liners. Custom packaging available upon request.

ADMIXUS® is a registered trademark of MiniFibers, Inc.

The above information is provided to describe typical values and does not constitute a product specification. MiniFIBERS warrants that for each Product sold, such Product will meet the standard specifications provided for that Product and will be of a quality consistent with the standard specifications. This is the sole warranty given with respect to the Product, and is given expressly in lieu of any other warranties, expressed or implied, including without limitation any implied or general warranty of merchantability or of fitness for a particular purpose. It is expressly understood that any technical advice or assistance that may be provided by MiniFIBERS is rendered without compensation, and MiniFIBERS assumes no obligation or liability for such advice or assistance given, or for results obtained.