



Technical Data Sheet

ADMIXUS® MST

FIBRILLATED HDPE
ADDITIVE FOR ASPHALT SEALERS

ADMIXUS® MST fibrillated HDPE is formulated to provide improved wet track abrasion in asphalt sealers. When incorporated into an asphalt sealer, ADMIXUS® MST fibrillated HDPE also forms a network that improves film formation and increases film tensile strength, strain and modulus.

Physical Characteristics

Average Fiber Length (µm)	600
Nominal Fiber Diameter (µm)	5
Surface Area (m ² /g)	12
Specific Gravity (g/cm ³)	0.96
Melting Point	275°F/135°C
Moisture Content	<2.0%
Packaging	Multi-walled kraft paper bags. 15 Lbs per bag; 50 bags per pallet.

ADMIXUS® is a registered trademark of MiniFibers, Inc.

The above information is provided to describe typical values and does not constitute a product specification. MiniFIBERS warrants that for each Product sold, such Product will meet the standard specifications provided for that Product and will be of a quality consistent with the standard specifications. This is the sole warranty given with respect to the Product, and is given expressly in lieu of any other warranties, expressed or implied, including without limitation any implied or general warranty of merchantability or of fitness for a particular purpose. It is expressly understood that any technical advice or assistance that may be provided by MiniFIBERS is rendered without compensation, and MiniFIBERS assumes no obligation or liability for such advice or assistance given, or for results obtained.